



ROG Strix SCAR 16 (2023) G634

Features	Tech Specs	Awards	Gallery	Support
----------	------------	--------	---------	---------





ROG Strix Scar 16 (2023) G634JY ROG Strix Scar 16 (2023) G634JZ

Operating System

Operating System

Windows 11 Pro

Windows 11 Pro

Processor

Processor

13th Gen Intel ® Core [™] i9-13980HX Processor 2.2 GHz (36M13th Gen Intel ® Core [™] i9-13980HX Processor 2.2 GHz (36MCache, up to 5.6 GHz, 24 cores: 8 P-cores and 16 E-cores)Cache, up to 5.6 GHz, 24 cores: 8 P-cores and 16 E-cores)

Graphics

Graphics

NVIDIA [®] GeForce RTX [™] 4090 Laptop GPU
ROG Boost: 2090MHz* at 175W (2040MHz Boost
Clock+50MHz OC, 150W+25W Dynamic Boost)
16GB GDDR6

NVIDIA[®] GeForce RTX[™] 4080 Laptop GPU ROG Boost: 2330MHz* at 175W (2280MHz Boost Clock+50MHz OC, 150W+25W Dynamic Boost) 12GB GDDR6

Display

Display

ROG Nebula HDR Display	ROG Nebula HDR Display
16-inch	16-inch
QHD+ 16:10 (2560 x 1600, WQXGA)	QHD+ 16:10 (2560 x 1600, WQXGA)
Anti-glare display	Anti-glare display
DCI-P3:100%	DCI-P3:100%
Refresh Rate:240Hz	Refresh Rate:240Hz
Response Time:3ms	Response Time:3ms
Mini LED	Mini LED
G-Sync	G-Sync
Pantone Validated	Pantone Validated
MUX Switch + NVIDIA [®] Advanced Optimus	MUX Switch + NVIDIA [®] Advanced Optimus
Support Dolby Vision HDR :Yes	Support Dolby Vision HDR :Yes

Memory	Memory
32GB DDR5-4800 SO-DIMM x 2	32GB DDR5-4800 SO-DIMM x 2
Max Capacity:64GB	Max Capacity:64GB
Support dual channel memory	Support dual channel memory

Storage	Storage
2TB + 2TB PCIe [®] 4.0 NVMe [™] M.2 Performance SSD (RAID 0)	2TB + 2TB PCIe [®] 4.0 NVMe [™] M.2 Performance SSD (RAID 0)

I/O Ports

I/O Ports

1x 3.5mm Combo Audio Jack

1x HDMI 2.1 FRL

1x 3.5mm Combo Audio Jack 1x HDMI 2.1 FRL

1x 2.5G LAN port	1x 2.5G LAN port
1x Thunderbolt $^{\tiny imes}$ 4 support DisplayPort $^{\tiny imes}$ / G-SYNC	1x Thunderbolt $\tilde{}$ 4 support DisplayPort $\tilde{}$ / G-SYNC
1x USB 3.2 Gen 2 Type-C support DisplayPort [™] / power	1x USB 3.2 Gen 2 Type-C support DisplayPort ** / power
delivery / G-SYNC	delivery / G-SYNC
2x USB 3.2 Gen 2 Type-A	2x USB 3.2 Gen 2 Type-A

Keyboard and Touchpad	Keyboard and Touchpad
Backlit Chiclet Keyboard Per-Key RGB	Backlit Chiclet Keyboard Per-Key RGB
Support NumberPad	Support NumberPad
Touchpad	Touchpad
Camera	Camera
720P HD camera	720P HD camera

Audio
Smart Amp Technology
Dolby Atmos
AI noise-canceling technology
Hi-Res certification
Support Microsoft Cortana near field/Far field
Built-in array microphone
4-speaker system with Smart Amplifier Technology

Network and	Communication
-------------	---------------

Network and Communication

Wi-Fi 6E(802.11ax) (Triple band) 2*2 + Bluetooth [®] 5.2 (*Bluetooth [®] version may change with OS version different.) Wi-Fi 6E(802.11ax) (Triple band) 2*2 + Bluetooth [®] 5.2

(*Bluetooth [®] version may change with OS version different.)

Battery

Battery

90WHrs, 4S1P, 4-cell Li-ion

90WHrs, 4S1P, 4-cell Li-ion

Power Supply

Power Supply

ø6.0, 330W AC Adapter, Output: 20V DC, 16.5A, 330W, Input:
100~240C AC 50/60Hz universal
TYPE-C, 100W AC Adapter, Output: 20V DC, 5A, 100W, Input:
100~240V AC 50/60Hz universal

ø6.0, 330W AC Adapter, Output: 20V DC, 16.5A, 330W, Input: 100~240C AC 50/60Hz universal TYPE-C, 100W AC Adapter, Output: 20V DC, 5A, 100W, Input: 100~240V AC 50/60Hz universal

Yes

Yes

Device Lighting	D

Aura Sync Rear Glow Aura Sync Light Bar Aura Sync logo Device Lighting

Aura Sync Rear Glow Aura Sync Light Bar Aura Sync logo

Weight

Weight

2.50 Kg (5.51 lbs)

2.50 Kg (5.51 lbs)

Dimensions (W \times D \times H)

Dimensions (W \times D \times H)

35.4 x 26.4 x 2.26 ~ 3.04 cm (13.94" x 10.39" x 0.89" ~ 1.20")

35.4 x 26.4 x 2.26 ~ 3.04 cm (13.94" x 10.39" x 0.89" ~ 1.20")

Security	Security
Trusted Platform Module (Firmware TPM)	Trusted Platform Module (Firmware TPM)
BIOS Administrator Password and User Password Protection	BIOS Administrator Password and User Password Protection

Included in the Box

Included in the Box

Marketing Giveaway (1 Customizable Armor Cap)	Marketing Giveaway (1 Customizable Armor Cap)
TYPE-C, 100W AC Adapter, Output: 20V DC, 5A, 100W, Input:	TYPE-C, 100W AC Adapter, Output: 20V DC, 5A, 100W, Input:
100~240V AC 50/60Hz universal (optional)	100~240V AC 50/60Hz universal (optional)
ROG Gladius III Mouse P514 (optional)	ROG Gladius III Mouse P514 (optional)
ROG backpack (optional)	ROG backpack (optional)
ROG Fusion II 300 (optional)	ROG Fusion II 300 (optional)
*Included accessories vary according to country and territory.	*Included accessories vary according to country and territory.
Please check with your local ASUS retailer for details	Please check with your local ASUS retailer for details

Note

Note

All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.

All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.



• This device supports Wi-Fi 6E, the newest standard in wireless networking. Please note that Wi-Fi 6E is not yet available in all regions. If your country has not opened up the necessary Wi-Fi bands, this device will use the best connection available. ROG will release a software update to enable Wi-Fi 6E when it's available in your region.

- The standard Asus test environment for battery life is as follows: Windows operating system, display module with 150 nits of brightness, lighting off, and other application settings.
- Video Playback: Testing is done with Wi-Fi/Bluetooth off, Windows Power Plan set to Balanced, Taskbar Power Mode set to Battery Saver, system volume at 67%, and video at full screen, 1080p resolution
- Web Browsing: Testing is done with Wi-Fi/Bluetooth, Windows Power Plan set to Balanced, Taskbar Power Mode set to Better Battery, and using the Weblooper Top50 website in Google Chrome to play the video with a refresh time of 10 seconds.
- Factors that affect battery life include laptop configuration, power settings, and the way it is used. Battery capacity fades with its cycle count and age.
- Quick-charging times apply when using the proper ASUS/ROG adapter included alongside the select model and the system is powered off (via the "shut down" command). In compatible scenarios, batteries can be recharged to 50% within 30 minutes under the optimal temperature range of 20-45 degrees Celsius. Charging times may vary +/- 10% due to system tolerance.
- The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.
- The actual HDMI version of the products should be checked in the product specifications page respectively.
- Products certified by the Federal Communications Commission and Industry Canada will be distributed in the United States and Canada. Please visit the ASUS USA and ASUS Canada websites for information about locally available products.
- All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.
- Specifications and features vary by model, and all images are illustrative. Please refer to specification pages for full details.
- PCB color and bundled software versions are subject to change without notice.
- Brand and product names mentioned are trademarks of their respective companies.
- Unless otherwise stated, all performance claims are based on theoretical performance. Actual figures may vary in real-world situations.
- The actual transfer speed of USB 3.0, 3.1, 3.2, and/or Type-C will vary depending on many factors including the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment.

> GAMING LAPTOPS > ROG STRIX > ROG STRIX SCAR 16 (2023) > G634JY

ABOUT ROG HOME NEWSROOM ACCESSIBILITY HELP

f y 🗨 🕨 🔑 🖸

Global/English

TERMS OF USE NOTICE PRIVACY POLICY ©ASUSTEK COMPUTER INC. ALL RIGHTS RESERVED.