OVERVIEW



| 1. Card reader | 6. Power connector |
|------------------------------|--|
| 2. USB 3.2 Gen 2 (Always On) | 7. Thunderbolt 4 |
| 3. USB 3.2 Gen 2 | 8. USB-C 3.2 Gen 2 |
| 4. USB 3.2 Gen 2 | 9. Headphone / microphone combo jack (3.5mm) |
| 5. HDMI | |

PERFORMANCE

Processor

Processor Family

13th Generation Intel[®] Core[™] i5 / i7 / i9 Processor

Processor^[1]

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | Processor Graphics |
|--------------------|------------------------------|---------|----------------------------------|----------------------------------|-------|----------------------------|
| Core i5- 13500H | 12 (4 P-core + 8 E- core) | 16 | P-core 2.6GHz / E-core 1.9GHz | P-core 4.7GHz / E-core 3.5GHz | 18MB | Intel Iris® Xe Graphics |
| Core i7- 13700H | 14 (6 P-core + 8 E-core) | 20 | P-core 2.4GHz / E-core 1.8GHz | P-core 5.0GHz / E-core 3.7GHz | 24MB | Intel Iris Xe Graphics |
| Core i9- 13900H | 14 (6 P-core + 8 E-core) | 20 | P-core 2.6GHz / E-core 1.9GHz | P-core 5.4GHz / E-core 4.1GHz | 24MB | Intel Iris Xe Graphics |

Notes:

[1] Intel Iris Xe Graphics capability requires system to be configured with dual-channel memory. On the system with singlechannel memory, Intel Iris Xe Graphics will function as Intel UHD Graphics.

Operating System

Operating System

- Windows® 11 Pro
- Windows 11 Home
- Windows 11 Home Single Language
- No operating system

Graphics

Graphics

| Graphics | Туре | Memory | Boost Clock | TGP | Key Features |
|---|----------|--------------|----------------|------|---|
| NVIDIA [®] GeForce RTX [™] 4050 Laptop GPU | | 6GB GDDR6 | 2370 MHz | 115W | Advanced Optimus, DLSS 3, Resizable BAR, Dynamic Boost 2.0, VR Ready, DirectX® 12 Ultimate |
| NVIDIA GeForce RTX 4060 Laptop GPU | Discrete | 8GB GDDR6 | 2370 MHz | 115W | Advanced Optimus, DLSS 3, Resizable BAR, Dynamic Boost 2.0, VR ready, DirectX 12 Ultimate |
| NVIDIA GeForce RTX 4070 Laptop GPU | Discrete | 8GB GDDR6 | 2175 MHz | 115W | Advanced Optimus, DLSS 3, Resizable BAR, Dynamic Boost 2.0, VR ready, DirectX 12 Ultimate |

Monitor Support

Monitor Support

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and USB-C®)

• HDMI supports up to 4K@60Hz

• USB-C supports up to 4K@60Hz

Chipset

Chipset

Intel SoC (System on Chip) platform

Memory

Max Memory^[1]

Up to 32GB (16GB soldered + 16GB SO-DIMM) DDR5-5200 offering

Memory Slots

One memory soldered to systemboard, one DDR5 SO-DIMM slot, dual-channel capable

Memory Type^[2]

DDR5-5200

Lenovo

Notes:

[1] The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

[2] Installed memory is actually 5600MHz but may run at 5200MHz due to processor limitation.

Storage

Storage Support^[1]

Up to two drives, 2x M.2 SSD • M.2 2280 SSD up to 1TB

Storage Slot

Two M.2 2280 PCIe[®] 4.0 x4 slots

Storage Type

| Disk Type | Interface | Offering | | |
|--------------|-------------------------|-------------|--|--|
| M.2 2280 SSD | PCIe NVMe®, PCIe 4.0 x4 | 512GB / 1TB | | |

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo storage offerings. The system may support larger storage as the technology develops.

Removable Storage

Card Reader

SD card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3306 codec

Speakers

Stereo speakers, 2W x2, audio by HARMAN, optimized with Nahimic Audio, Smart Amplifier (AMP)

Microphone

Dual-microphone array

Camera

FHD 1080p, with E-shutter, fixed focus

Battery

Battery

Integrated Li-Polymer 99.9Wh battery, supports Super Rapid Charge (10min charge 0~30% capacity, 30min charge 0~70% capacity, 80min charge 0~100% capacity)

Max Battery Life^[1]

MobileMark® 2018: 8.4 hr Local video (1080p) playback@150nits: 9.1 hr

Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, MobileMark 25, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter

230W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz

Special Features

Special Features^[1]

Legion Coldfront 5.0 cooling system

• AI Chip: LA2-Q

Notes:

[1] This chip powers Lenovo AI Engine+, which uses software-based machine learning via its Lenovo Vantage software to monitor in-game frame rates and adjust the internal components to target the highest performance.

DESIGN

Display

Display^{[1][2]}

| Size | Resolution | Touch | Туре | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Refresh Rate | Viewing Angle (L/R/U/D) | Key Features |
|------|----------------------|-------|------|------------|----------------|-----------------|-------------------|--------------------|-----------------|----------------------------|--|
| 16″ | WQXGA (2560x1600) | None | IPS | 300 nits | Anti- glare | 16:10 | 1200:1 | 100% sRGB | | 89°/89°/89°/89° | Refresh rate 165Hz, Dolby® Vision™, NVIDIA G- SYNC®, Advanced Optimus support, TÜV Low Blue Light |
| 16″ | WQXGA (2560x1600) | None | IPS | 500 nits | Anti- glare | 16:10 | 1200:1 | 100% sRGB | | 89°/89°/89°/89° | Refresh rate 240Hz, DisplayHDR™ 400, Dolby Vision, NVIDIA G- SYNC, Advanced Optimus support, TÜV Low Blue Light |
| 16″ | 3.2K (3200x2000) | None | IPS | 430 nits | Anti- glare | 16:10 | 1200:1 | 100% DCI- P3 | 165 Hz | 89°/89°/85°/85° | Dolby Vison, NVIDIA G- SYNC, Advanced Optimus support, TÜV Low Blue Light |

Color Calibration

X-Rite® factory color calibration

Touchscreen

Non-touch

Notes:

[1] California Electronic Waste Recycling Fee

In California USA, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, please go to https://www.calrecycle.ca.gov/Electronics/Consumer. [2] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Keyboard

• Storm grey models: 6-row, spill-resistant, multimedia Fn keys, numeric keypad, storm grey keycaps

• Glacier white models: 6-row, spill-resistant, multimedia Fn keys, numeric keypad, white keycaps

Keyboard Backlight

- White backlight
- Per-key RGB backlight

Touchpad

Buttonless glass surface multi-touch touchpad, 75 x 120 mm (2.95 x 4.72 inches)

Mechanical

Dimensions (WxDxH)^[1]

357.7 x 259.3 x 17.6-19.9 mm (14.08 x 10.21 x 0.69- 0.78 inches)

Weight^[2]

Around 2 kg (4.4 lbs)

Case Color

- Glacier white
- Storm grey

Surface Treatment

Anodizing

Case Material

Aluminium (top), aluminium (bottom)

System Lighting

RGB lighting on power button

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet

No onboard Ethernet

WLAN + Bluetooth®[1][2]

- Wi-Fi[®] 6E, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 card
- Intel Killer Wi-Fi 6E AX1675i, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 Card

Notes:

[1] Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitations.

[2] Wi-Fi 6E full features might be limited by country-level restrictions.

6GHz Wi-Fi 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi 6E, and the regional regulatory certifications & spectrum allocation.

Ports^{III}

Standard Ports

- 2x USB 3.2 Gen 2
- 1x USB 3.2 Gen 2 (Always On)
- 1x USB-C 3.2 Gen 2 (support data transfer, Power Delivery 100W and DisplayPort™ 1.4)
- 1x Thunderbolt[™] 4 / USB4[®] 40Gbps (support data transfer, Power Delivery 100W and DisplayPort 1.4)
- 1x HDMI 2.1, up to 8K/60Hz
- 1x Card reader
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Power connector

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

Lenovo

USB 2.0: 480 Mbit/s; USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s; USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s; USB4 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s; USB4 40Gbps (USB 40Gbps): 40 Gbit/s; Thunderbolt 3/4: 40 Gbit/s.

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in SoC

Fingerprint Reader

Touch style fingerprint reader integrated in power button

BIOS Security

- Administrator password
- Power-on password
- Hard disk password
- Self-healing BIOS

Other Security

E-shutter

SERVICE

Warranty

Base Warranty

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
 Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 Maximum temperature when operations
- Maximum temperature when operating under the unpressurized condition: 31.3 $^{\circ}\text{C}$ (88 $^{\circ}\text{F}$) Humidity
- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] Note: When you charge the battery, its temperature must be no lower than 10°C (50°F).

CERTIFICATIONS

Green Certifications^{III}

Green Certifications

- ErP Lot 3
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or selfdeclaration.

Other Certifications

Other Certifications

TÜV Rheinland[®] Low Blue Light (Hardware Solution)

- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

Lenovo PSREF Product Specifications Reference







